


AirLiner™ Wireless Slate

Specifications – Model WS100

Physical Specifications

Size	11" W x 10 1/8" H x 1" D (27.9 cm x 25.7 cm x 2.5 cm)
Active Screen Area	7 3/4" W x 6" H (19.7 cm x 15.2 cm) 9 3/4" (24.8 cm) diagonal
Weight	2 lb. (0.9 kg)
Shipping Size	11 1/2" W x 13 1/4" H x 3 3/4" D (29.2 cm x 33.7 cm x 9.5 cm)
Shipping Weight	4 lb. (1.8 kg)



All dimensions +/- 1/8" (0.3 cm). All weights +/- 2 lb. (0.9 kg).

Standard Features

Software	SMART Notebook software included. See the SMART Notebook software specifications for a complete list of system requirements. Software upgrades are available at www2.smarttech.com/st/en-US/Support/SBS/ .
Communication Interface	Bluetooth® wireless technology using HID protocol
Electromagnetic Technology	Allows you to rest your hand and write naturally on the transparent overlay, without interfering with the digital ink
Maximum Report Rate	100 points per second
Coordinate Resolution	2,032 lpi (80 lpmm)
Bluetooth Adapter	Class 2 adapter allows wireless connectivity with an expected range of 52' (15.9 m) and a maximum range in free space of 164' (50.0 m)
Underlay and Icon Strip	Allows you to switch between the eraser, electronic ink colors (black, blue, red and green), right-click, floating keyboard, screen capture tools and SMART Board software control panel
Anti-Slip Feet	Four anti-slip rubber feet keep the AirLiner™ wireless slate stable when working on flat surfaces.
Buttons	Two programmable buttons open Floating Tools and Notebook software by default.
Pen	Battery-free tethered pen. +/- 0.5 mm accuracy with an average reading height of 5 mm.
Mouse	Battery-free wireless fingerwheel mouse with continuous rotation, 24 notches per revolution
Power Requirements	6V DC, 450mA from Class 2 power adapter
Power Adapter	Input Voltage: 100V–240V AC, 50 Hz–60 Hz, 0.3 VA Output Voltage: 6V DC, 1.0A
Battery	Rechargeable lithium ion battery with 25–30 hours of life per charge, 3.7V, 1800mA
Certifications and Compliance	CE, FCC, RoHS (Europe), WEEE
Warranty	Two-year limited warranty

Storage and Operating Specifications

Storage	14°F–140°F (-10°C–60°C) with 20%–90% humidity, non-condensing
Operating	41°F–104°F (5°C–40°C) with 20%–80% humidity, non-condensing

SMART Order Numbers

WS100	AirLiner wireless slate
WS100-BNDL	AirLiner wireless slate (when purchased with a SMART Board 600 series interactive whiteboard)

Dimensions

