



## DS-2CD2012-I 1.3MP IR Mini Bullet Camera



### Key features

- 1.3 megapixel high resolution
- HD video output
- Low illumination
- IP66 rating
- IR range: up to 30m
- True day / night

### Dimensions



### Specifications

DS-2CD2012-I	
<b>Camera</b>	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @F1.2, AGC ON 0 lux with IR
Shutter time	1/25s ~ 1/100,000s
Lens	6mm @F1.2 (4mm, 12mm optional)
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
<b>Compression Standard</b>	
Video compression	H.264 / MPEG4 / MJPEG
Bit rate	32 Kbps ~ 16 Mbps
<b>Image</b>	
Max. Image Resolution	1280 × 960
Frame rate	50Hz: 25fps (1280 × 960), 25fps (1280 × 720) 60Hz: 30fps (1280 × 960), 30fps (1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
<b>Network</b>	
Network storage	NAS (iSCSI optional)
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
<b>Interface</b>	
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
<b>General</b>	
Operating conditions	-10 °C ~ 60 °C (14°F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	max. 4W (ICR on: max. 5.5W)
Weather proof rating	IP66
IR range	Up to 30m
Dimension	60.4 x 76.5 x 138.1mm
Weight	300g

### Available model

DS-2CD2012-I

\* Product picture and technical specs subject to change without previous notice.  
For further information, please contact our local sales team.