


DS-4002/04MDI+ Matrix Compression Card



Key Features

- H.264 video stream supported
- Up to 4CIF resolution decoding
- Up to 4-ch video&audio BNC outputs
- Up to 4x4 mutiplex windows display
- Picture-In-Picture display
- PCI 2.2 standard

Specifications

	DS-4002MDI+	DS-4004MDI+
Video/Audio output		
Support Video compression Standard	H.264	
Video Output	2-ch	4-ch
Video Output Interface	BNC (1.0 Vp-p, 75 Ω)	
Video Standard	PAL/NTSC	
Resolution	2-ch 4CIF Or 4-ch DCIF / 2CIF Or 8-ch CIF / QCIF	4-ch 4CIF or 8-ch DCIF / 2CIF or 16-ch CIF / QCIF
Frame rate	PAL: 25 fps; NTSC: 30 fps	
Support audio compression standard	OggVorbis	
Audio output	2-ch PCM, mono	4-ch, mono
Audio output interface	BNC (Linear Level, 600 Ω)	
General		
PCI standard	PCI 2.2	
Power consumption	< 10 w	< 16 w
Dimensions	168 x 101 mm (6.61" x 3.98")	220 x 89 mm (8.66" x 3.50")
System requirements		
OS	Windows 2000/XP/2003/Vista/7/Linux	
CPU	Intel C4/P4/Core2/Core4 Series	
Motherboard	Based on Intel 845/865/915/925/945/965/G31/G33/P31/P35/P43/P45 Series. Please refer to the compatible list on the Hikvision website	
Memory	512MB or above	
Display adapter	ATI Radeon X1650/X1600/X1550/X1300/X800/X600/X550/HD2400/HD2600 ATI Radeon 7000/7200/7500/8500 /9000/9200 /9500/9600 NVIDIA GeForce 8600GT/8500GT/8400GS/7600/7300LE/6600LE/6200LE Please refer to the compatible list on the Hikvision website	