

Clear Horn Speakers

CH-510/522/530/532




CH-510(10W)
4" Full Range

CH-530(30W)
4" Full Range

CH-522
4" Full Range

CH-532
4" Coaxial Cone



Features

- Indoor or outdoor use
- Coaxial-type 2way system
- Wide frequency range with remarkable vocal clarity
- Excellent for public address systems
- Easy installation
- Dispersion control

Spec	CH-510	CH-522	CH-530	CH-532
Rated Power	10W	20W	30W	30W
Impedance	COM(Black / Green Yellow)	COM(Black / Green Yellow)	COM(Black / Green Yellow)	COM(Black / Green Yellow)
	1kΩ (White / Gyan)	500Ω (White / Gyan)	165Ω (White / Gyan)	165Ω (White / Gyan)
	2kΩ (Green / Brown)	1kΩ (Green / Brown)	333Ω (Green / Brown)	333Ω (Green / Brown)
Frequency Response	150Hz-18kHz	140Hz-12kHz	100Hz-20kHz	180Hz-9kHz
SPL (1W/m)	93dB	91dB	93dB	93dB
Weight	3.3kg / 7.3lb	3.7kg / 8.1lb	3.5kg / 7.7lb	4kg / 8.8lb
Dimensions (W×H×D)	294 × 209 × 326mm / 11.6 × 8.2 × 12.8in			

Paging Horn Speakers

HS-S20/20/30/50/30RT/40RT



HS-S20



HS-20



HS-30



HS-50



HS-30RT



HS-40RT

Spec	HS-S20
Rated Power	20W
IP Rate	IP65
Impedance	500Ω(White)
	1kΩ(Green)
Frequency Response	350Hz - 5.5kHz
SPL (1W/m)	106dB
Weight	1.5kg / 3.3lb
Dimensions<DIA×LENGTH>	ø169 × 230mm / ø6.7 × 9in

Spec	HS-20	HS-30	HS-50
Rated Power	20W	30W	50W
IP Rate	IP65		
Impedance	500Ω(White)	330Ω(White)	200Ω(White)
	1kΩ(Green)	660Ω(Green)	400Ω(Green)
Frequency Response	350Hz - 5.5kHz	250Hz - 5kHz	250Hz - 5kHz
SPL (1W/m)	106dB	106dB	106dB
Weight	2.4kg / 5.3lb	2.7kg / 6lb	3.1kg / 6.8lb
Dimensions<DIA×LENGTH>	ø250 × 280mm	ø280 × 330mm	ø320 × 350mm
	ø10 × 11in	ø11 × 13.7in	ø12.6 × 13.7in

Spec	HS-30RT	HS-40RT
Rated Power	30W	40W
IP Rate	IP65	
Impedance	330Ω(White)	250Ω(White)
	660Ω(Green)	500Ω(Green)
Frequency Response	250Hz - 5kHz	250Hz - 5kHz
SPL (1W/m)	106dB	106dB
Weight	2.9kg / 6.4lb	3kg / 6.6lb
Dimensions(W×H×D)	320 × 210 × 365mm / 12.6 × 8.2 × 14.3in	