


## DS-2CD2032-I


## 3MP IR Mini Bullet Camera



### Key features

- 3 Megapixel High Resolution
- Full HD1080p Video Output
- Low Illumination
- 3D DNR & DWDR & BLC
- IP66 Rating
- IR Range: up to 30m
- True Day / Night

### Dimensions



### Specifications

DS-2CD2032-I	
<b>Camera</b>	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.19 lux @F2.0, AGC ON 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm@F2.0 (6mm, 12mm optional) Angle of view: 75.8°
Lens mount	M12
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
<b>Compression Standard</b>	
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
<b>Image</b>	
Max. Image Resolution	2048 × 1536
Frame rate	60Hz: 15fps (2048 × 1536), 30fps (1920 × 1080), 30fps (1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
<b>Network</b>	
Network storage	NAS
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
<b>Interface</b>	
Communication interface	1 RJ45 10 M / 100 M Ethernet interface
<b>General</b>	
Operating conditions	-30 °C ~ 60 °C (-22 °F ~140 °F) Humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 5W (7W with ICR on)
Weather proof rating	IP66
IR range	Up to 30m
Dimension	60.4 x 76.5 x 138.1mm
Weight	300g

### Available model

DS-2CD2032-I